



# 2016 Competitive Testing Results

## DOMINATOR EXTRA AGGRESSIVE STRIPPING PAD

|   |     | Competitor A | Competitor B |
|---|-----|--------------|--------------|
| <b>Durability****</b><br>% weight loss post use             | 3   | 1            | 5            |
| <b>Finish Removal</b><br>Number of passes to remove 5 coats | 3   | 2            | 7            |
| <b>Weight</b><br>oz. per sq. yard                           | 57  | 44           | 64           |
| <b>Thickness (mm)</b>                                       | 24  | 13           | 18           |
| <b>Tensile (lb/f)*</b>                                      | 115 | 44           | 82           |

## BLACK STRIPPING PAD

|   |    | Competitor A | Competitor B |
|---|----|--------------|--------------|
| <b>Durability****</b><br>% weight loss post use             | 3  | 4            | 5            |
| <b>Finish Removal</b><br>Number of passes to remove 5 coats | 4  | 3            | 8            |
| <b>Weight</b><br>oz. per sq. yard                           | 50 | 59           | 52           |
| <b>Thickness (mm)</b>                                       | 24 | 21           | 25           |
| <b>Tensile (lb/f)*</b>                                      | 77 | 44           | 69           |

## AQUA BURNISHING

|   |    | Competitor A | Competitor B |
|---|----|--------------|--------------|
| <b>Durability***</b><br>% weight loss post use  | 9  | 10           | 13           |
| <b>Weight</b><br>oz. per sq. yard               | 32 | 34           | 33           |
| <b>Thickness (mm)</b>                           | 26 | 26           | 27           |
| <b>Tensile (lb/f)*</b>                          | 67 | 54           | 69           |
| <b>% Gloss Increase</b><br>Propane 2000 rpms**  | 64 | 47           | 56           |
| <b>% Gloss Increase</b><br>Battery 2000 rpms**  | 55 | 55           | 34           |
| <b>% Gloss Increase</b><br>Electric 2000 rpms** | 77 | 33           | 23           |

## PORKO PLUS

|   |    | Competitor A | Competitor B |
|---|----|--------------|--------------|
| <b>Durability***</b><br>% weight loss post use  | 11 | 9            | 18           |
| <b>Weight</b><br>oz. per sq. yard               | 37 | 41           | 24           |
| <b>Thickness (mm)</b>                           | 26 | 24           | 27           |
| <b>Tensile (lb/f)*</b>                          | 89 | 108          | 33           |
| <b>% Gloss Increase</b><br>Propane 2000 rpms**  | 56 | 29           | 47           |
| <b>% Gloss Increase</b><br>Battery 2000 rpms**  | 48 | 37           | 11           |
| <b>% Gloss Increase</b><br>Electric 2000 rpms** | 24 | 11           | 6            |

## RED BUFF

|   |    | Competitor A | Competitor B |
|---|----|--------------|--------------|
| <b>Durability****</b><br>% weight loss post use                     | 14 | 9            | 17           |
| <b>Cleaning Test</b><br>No. of passes to remove grease pencil marks | 4  | 4            | 6            |
| <b>Weight</b><br>oz. per sq. yard                                   | 29 | 34           | 34           |
| <b>Thickness (mm)</b>   | 28 | 27           | 25           |
| <b>Tensile (lb/f)*</b>  | 65 | 63           | 73           |

\* **Tensile:** Pounds of force per inch width to pull pad apart.

\*\* **Gloss:** The gloss is determined using a ETC-CT60 Micro-Gloss 60° Meter which measures the amount of reflection when light is directed on a test surface at a 60° angle.

\*\*\* **Durability (Aqua and Porko Plus):** The test is 13" pads run for 5 hrs. @20,000 ft.<sup>2</sup>/hr. with a 200 rpm Auto Scrubber w/200 lb. downforce on unsealed concrete.

\*\*\*\* **Durability (Dominator, Black, and Red):** The test is 20" pads run for 5 hrs. @20,000 ft.<sup>2</sup>/hr. with a 2000 rpm propane machine on unsealed concrete.